

ULTRACARE KERAPOXY CLEANER

Ready to use special cleaning product to remove epoxy residues



BENEFITS AND FEATURES

- Ready to use
- Quick and easy to apply
- High performance
- Epoxy residue removal
- Ideal for cleaning immediately after and during installation

CO₂e FULLY OFFSET PRODUCTS

Residual Greenhouse Gas emissions measured throughout the life cycle of this product using Life Cycle Assessment (LCA) methodology, verified and certified with EPDs, have been offset for the year 2026 through the acquisition of carbon credits in support of forestry protection projects. For more details on emission calculations and offsetting projects, visit mapei.com.

DESCRIPTION

UltraCare Kerapoxy Cleaner can be used both for fresh cleaning operations and after completing laying work to remove traces and stains of epoxy residues.

It will remove traces and marks of all epoxy grouts, including MAPEI **Kerapoxy**, **Kerapoxy CQ**, **Kerapoxy Easy Design**, from ceramic and glass mosaic coating layers.

WHERE TO USE

UltraCare Kerapoxy Cleaner is a simple to use product that easily removes traces of epoxy grout from porcelain, glazed ceramic, glass mosaics and non-absorbent surfaces. It is also a ready to use product, so no dilution is required. It can be used immediately after grouting as well as being able to remove cured residues.

It is also suitable for cleaning the tools used to apply epoxy grouts.

TECHNICAL CHARACTERISTICS

UltraCare Kerapoxy Cleaner is a concentrated liquid detergent. **UltraCare Kerapoxy Cleaner** is used to remove residues, stains and marks of epoxy grout without giving off hazardous fumes.

If used correctly, **UltraCare Kerapoxy Cleaner** does not damage either the coating surface or grouted joints.

RECOMMENDATIONS

- Do not use on polished marble or stone and, in case of application on natural stone, make a preliminary test on a hidden area of the surface.
- Do not use on wood.
- Do not use on methacrylate baths.
- Before using **UltraCare Kerapoxy Cleaner** on materials with an unknown surface resistance, test the product beforehand to make sure it does not damage the surface.
- Before using the product, protect all surfaces which could be damaged in direct contact with the product.

APPLICATION PROCEDURE

UltraCare Kerapoxy Cleaner is diluted and ready to use. Apply it directly onto the surface to be cleaned or onto the traces of grout residue and leave for a few minutes. Then work over the surface with a Scotch-Brite® pad. Remove the solution and then rinse thoroughly with clean water. **UltraCare Kerapoxy Cleaner** can be added to the cleaning water at a dilution of 1:100 to make the cleaning process more effective. The product is particularly efficient on fresh grout. If cleaning is carried out a few hours after applying the grout, it may be necessary to leave it standing for longer (at least 15-20 minutes) or you may need to repeat the cycle.

For residues that have cured on the surface over time or if residues persist then use **UltraCare Epoxy Off Gel**. Please refer to the relative technical data sheet for the application method.

For applications on flooring it is possible to carry out cleaning with single disc cleaning machine.

CONSUMPTION

Depending on the needs, it can vary based on the degree and type of dirt and the surface to be treated.

PACKAGING

UltraCare Kerapoxy Cleaner is available in 750 ml spray bottles and 5 litres tanks.

STORAGE

UltraCare Kerapoxy Cleaner may be stored for up to 36 months in its original, sealed packaging in a cool place.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Instructions for the safe use of our products can be found on the latest version of the Safety Data Sheet, available from our website www.mapei.com.

PRODUCT FOR PROFESSIONAL USE.

TECHNICAL DATA (typical values)

PRODUCT IDENTITY

Consistency:	liquid
Colour:	opalescent
Density:	1.10 g/cm ³
pH:	11
Application temperature range:	0°C to +40°C
Waiting time before rinsing:	up to 15-20 minutes

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.com

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.

The most up-to-date TDS can be downloaded from our website www.mapei.com.

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.

Mapei S.p.A.

Via Cafiero, 22, 20158, Milano



+39-02-376731



www.mapei.com



mapei@mapei.it

11001-7-2026 en (IT)

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution

