

ULTRACARE FUGA FRESCA GROUT REFRESH

Polymeric paint to refresh the colour of the cementitious grout joints between tiles



CO₂e FULLY OFFSET PRODUCTS

Residual Greenhouse Gas emissions measured throughout the life cycle of this product using Life Cycle Assessment (LCA) methodology, verified and certified with EPDs, have been offset for the year 2026 through the acquisition of carbon credits in support of forestry protection projects. For more details on emission calculations and offsetting projects, visit mapei.com.

BENEFITS AND FEATURES

- Quick and easy to apply; shake/stir well before use
- Excellent covering power
- Protects joints and makes routine cleaning easier
- Available in 40 colours from the MAPEI coloured grouts range
- Residual Greenhouse Gas emissions fully offset

WHERE TO USE

UltraCare Fuga Fresca is a ready-to-use paint for internal areas which is quickly and easily applied to rejuvenate, refresh and modify the colour of cementitious grout joints between tiles.

Some application examples

UltraCare Fuga Fresca is used to eliminate irregularities in the colour of grout-joints caused, for example, by incorrect application of the grout, or to eliminate unsightly stains caused during use.

TECHNICAL CHARACTERISTICS

UltraCare Fuga Fresca is a water-based polymeric, acrylic resin-based paint which, thanks to its special characteristics and excellent covering qualities, allows joints with a uniform colour to be produced with lower water absorption that are easy to clean.

RECOMMENDATIONS

- Do not use for external applications or on surfaces subjected to continuous immersion (swimming pools, basins, etc.).
- If the product is used on terracotta floors or on stone material with a porous, absorbent surface, it must only be applied on the joints to avoid staining the tiles.
- Apply the product on fully cured cementitious grouts (time varies according to the specific type of grout).
- Do not use on epoxy grouts or on expansion joints sealed with silicone or polyurethane-based products.
- Do not use **UltraCare Fuga Fresca** to consolidate friable grout or those with poor mechanical strength due to inadequate hydration.
- If the colour difference between the original colour and the new colour is too great, it may be necessary to apply more than one coat.

APPLICATION PROCEDURE

Sponge applicator bottle

Shake the bottle well before use. Unscrew the cap and apply the product by pressing the sponge applicator lightly on the surface of the joints, which must be clean and free of loose parts, mould and calcium deposits. Wait a few minutes until the product applied on the joints is dry (according to actual environmental conditions). Remove any traces of the product from the edges of the tiles using a damp sponge. After use, thoroughly clean the sponge applicator on the bottle.

Bucket

The product is ready-for-use.

Mix the product in the bucket thoroughly before use. Using a brush of suitable size, spread the product on the surface of the joints, which must be clean and free of loose parts, mould and calcium deposits. Wait a few minutes until the product applied on the joints is dry. Remove any traces of the product from the edges of the tiles using a damp sponge.

COLOURS AVAILABLE

1 kg bucket, available in colour 110 only.

160 g sponge applicator bottle, available in all 40 colours of the MAPEI range.

UltraCare Fuga Fresca		
100	WHITE	
103	MOON WHITE	
111	SILVER GREY	
123	ANCIENT WHITE	
112	MEDIUM GREY	
113	CEMENT GREY	
114	ANTHRACITE	
127	ARCTIC GREY	
110	MANHATTAN 2000	

187	LINEN	
176	GREEN-GREY	
174	TORNADO	
125	CASTLE GREY	
119	LONDON GREY	
163	LIGHT LILAC	
168	CERULEAN	
167	AVIO	
169	STEEL BLUE	
172	SPACE BLUE	
177	SAGE	
130	JASMINE	
131	VANILLA	
137	CARIBBEAN	
132	BEIGE 2000	
138	ALMOND	
141	CARAMEL	
142	BROWN	
189	SPELT	
133	SAND	
134	SILK	
188	BISCUIT	
135	GOLDEN DUST	
152	LIQUORICE	
144	CHOCOLATE	
149	VOLCANO SAND	
145	TERRA DI SIENA	

143	TERRACOTTA	
136	MUD	
120	BLACK	
150	YELLOW	

N.B.: Due to the printing processes involved, the colours should be taken as merely indicative of the shades of the actual product

CONSUMPTION

Dependant on the size of the tiles and joints.

PACKAGING

1 kg bucket and 160 g sponge applicator bottle.

STORAGE

2 years in its original, sealed container stored under normal conditions.
Protect from frost.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Instructions for the safe use of our products can be found on the latest version of the Safety Data Sheet, available from our website www.mapei.co.uk

PRODUCT FOR PROFESSIONAL USE.

TECHNICAL DATA (typical values)

PRODUCT IDENTITY

Consistency:	thick liquid
Colours:	available in 40 colours
Density:	1.37 g/cm ³
pH:	9
Dry solids content:	62%
Brookfield viscosity:	8 Pa.s (# 6 - 10 rpm)
Covering capacity (contrast ratio):	96.93
Dirt pick-up (UNI 10792):	ΔE* 0.27
Abrasion resistance (DIN 53778):	> 10,000 cycles
Weatherometer resistance (ASTM G155), cycle 1:	ΔE* 0.04
Application temperature range:	from +5°C to +35°C
Ready for foot traffic:	2 hours
Waiting time before putting the treated surface in contact with water:	24 hours

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.co.uk

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.

The most up-to-date TDS can be downloaded from our website www.mapei.co.uk

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.

Mapei U.K. Ltd

Mapei House Steel Park Road - Halesowen, West Midlands, B62 8HD



+44-121-5086970



www.technical-uk@mapei.co.uk



info@mapei.co.uk

11009-7-2026 (UK)

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution

